# Siemens CLINITEK Advantus Urinalysis Analyzer



## **OVERVIEW**

Respond to demands for higher productivity and high quality with the CLINITEK Advantus® Analyzer. Streamline your workflow with flexible operation, Immediate start-up, Automatic calibration, Network ready, and Widest range of test options with Added QC features.

## **FEATURES**

- New, easy-to-use color touchscreen
- Ability to consolidate microscopy results onto one patient record
- Increased control with automatic QC prompting and QC lockout capability to ensure compliance
- Testing flexibility with simple, one-touch switching between different strip configurations
- A total of three sieve functions confirmatory and microscopic to flag abnormal results for quick review
- Convenient data retrieval for up to 500 patients by patient ID, and 200 control results

#### **SPECIFICATIONS**

Automatic Measurement

Test FormatDry chemistry reagent stripsTest MeasurementColor change measured by

Urine color

reflectance photometry
Dual readings at reactive and
reference wavelengths
Automatically adjusts for urine

automatically adjusts for di

color

**Dimensions (in.)** 12.75 (h) x 15.75 (w) x 13.75 (d)

**Weight** 7.2 kg (16 lbs)

Power Requirements100 V to 240 V; 50/60 HzLine Leakage Current<0.5 mA in normal condition</th>

<3.5 mA in single fault condition

Maximum Power Input 72 VA

**Ambient Operating** 18°C to 30°C (64°F to 86°F)

Temperature Range
Ambient Operating

perating 20% to 80% relative humidity

Humidity Range

Compliance UL, CE, EMC
Sample Loading Self-paced, not dictated by

analyzer

STAT Sample Handling One-touch STAT interrupt

capability

Sample ProcessingSingle or batch modeSample ID EntryManual, bar code, or

downloaded from LIS

CalibrationAutomatic with every stripMemory500 patient records plus 200

controls

Interfaces ASTM (CCS) format and

emulates CLINITEK 200 and

CLINITEK 200+

**Display** Color LCD touchscreen, 5.7 in

(14.5 cm), 320 horizontal by 240 vertical pixels (QVGA) 10/100 Mbit, bidirectional

Ethernet Connection Onboard Printer Bar Code

10/100 Mbit, bidirectional 24-character thermal printer Meets ASTM E1466-92

standards, available with PC

wedge/PS2

Keyboard External PC keyboard

option/PS2

**External Printer** Printer interface: parallel port

#### **Contact Us for More Information:**

- info@techneal.com
- 909-465-6325
- www.techneal.com

